

Package: bate (via r-universe)

August 26, 2024

Title Computes Bias-Adjusted Treatment Effect

Version 0.1.0

Description Compute bounds for the treatment effect after adjusting for the presence of omitted variables in linear econometric models, according to the method of Basu (2022) [arXiv:2203.12431](https://arxiv.org/abs/2203.12431). You supply the data, identify the outcome and treatment variables and additional regressors. The main functions will compute bounds for the bias-adjusted treatment effect. Many plot functions allow easy visualization of results.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

LazyData true

Imports ggplot2, concaveman, dplyr, stats, magrittr, tidyselct, purrr, latex2exp, sensemakr

Suggests rmarkdown, knitr, vtable

VignetteBuilder knitr

URL <https://github.com/dbasu-umass/bate/>,
<https://rpubs.com/dbasu/bate/>

Repository <https://dbasu-umass.r-universe.dev>

RemoteUrl <https://github.com/dbasu-umass/bate>

RemoteRef HEAD

RemoteSha 46798901e6e9f26578f9366c7c03b1434e4745fa

Contents

cinhaz	2
collect_par	3

cplotbias	4
delfplot	5
dplotbate	6
expand_border	7
get_border	8
mycubic	9
mydisc	9
NLSY_BW	10
NLSY_IQ	11
osterbds	12
osterdelstar	13
ovbias	14
ovbias_lm	15
ovbias_par	17
partocoef	18
selectroot	19
split_nurr	20
urrplot	20
Index	22

cinhaz	<i>Conduct partial and total R2-based sensitivity analysis</i>
--------	--

Description

Conduct partial and total R2-based sensitivity analysis

Usage

```
cinhaz(kd, ky, data, outcome, treatment, bnch_reg, other_reg, alpha)
```

Arguments

kd	relative strength of the confounder in explaining variation in treatment as compared to benchmark covariate(s)
ky	relative strength of confounder in explaining variation in outcome as compared to benchmark covariate(s)
data	data frame
outcome	outcome variable
treatment	treatment variable
bnch_reg	benchmark covariate(s)
other_reg	other covariates in the model (other than treatment and benchmark covariates)
alpha	significance level for hypothesis test (H0: true effect = 0)

Value

A data frame with results

Examples

```
## Load library
library(sensemakr)
## Conduct analysis
cinhaz(kd=1,ky=1,data=darfur,outcome = "peacefactor",
treatment = "directlyharmed", bnch_reg = "female",
other_reg = c("village","age","farmer_dar","herder_dar","pastvoted","hhsiz_darfur"),
alpha=0.05)
```

collect_par	<i>Collect parameters from the short, intermediate and auxiliary regressions</i>
-------------	--

Description

Collect parameters from the short, intermediate and auxiliary regressions

Usage

```
collect_par(data, outcome, treatment, control, other_regressors = NULL)
```

Arguments

data	A data frame.
outcome	The name of the outcome variable (must be present in the data frame).
treatment	The name of the treatment variable (must be present in the data frame).
control	Control variables to be added to the intermediate regression.
other_regressors	Subset of control variables to be added in the short regression (default is NULL).

Value

A data frame with the following columns:

beta0	Treatment effect in the short regression
R0	R-squared in the short regression
betatilde	Treatment effect in the intermediate regression
Rtilde	R-squared in the intermediate regression
sigmay	Standard deviation of outcome variable
sigmax	Standard deviation of treatment variable
taux	Standard deviation of residual in auxiliary regression

Examples

```
## Load data set
data("NLSY_IQ")

## Set age and race as factor variables
NLSY_IQ$age <- factor(NLSY_IQ$age)
NLSY_IQ$race <- factor(NLSY_IQ$race)

## Collect parameters from the short, intermediate and auxiliary regressions
parameters <- collect_par(
  data = NLSY_IQ, outcome = "iq_std",
  treatment = "BF_months",
  control = c("age", "sex", "income", "motherAge", "motherEDU", "mom_married", "race"),
  other_regressors = c("sex", "age"))

## See results
(parameters)
```

cplotbias

Create contour plot of bias

Description

Create contour plot of bias

Usage

```
cplotbias(data)
```

Arguments

data A data frame that is the output from the "ovbias" function.

Value

A plot object created with ggplot

Examples

```
## Load data set
data("NLSY_IQ")

## Set age and race as factor variables
NLSY_IQ$age <- factor(NLSY_IQ$age)
NLSY_IQ$race <- factor(NLSY_IQ$race)

## Collect parameters from the short, intermediate and auxiliary regressions
parameters <- collect_par(
```

```
data = NLSY_IQ, outcome = "iq_std",
treatment = "BF_months",
control = c("age", "sex", "income", "motherAge", "motherEDU", "mom_married", "race"),
other_regressors = c("sex", "age"))

## Set limits for the bounded box
Rlow <- parameters$Rtilde
Rhigh <- 0.61
deltalow <- 0.01
deltahigh <- 0.99
e <- 0.01

## Not run:
## Compute bias and bias-adjusted treatment effect
OVB <- ovbias(
  parameters = parameters,
  deltalow=deltalow,
  deltahigh=deltahigh, Rhigh=Rhigh,
  e=e)

## Contour Plot of bias over the bounded box
p2 <- cplotbias(OVB$Data)
print(p2)

## End(Not run)
```

delfplot

Plot graph of function $\delta=f(R_{max})$

Description

Plot graph of function $\delta=f(R_{max})$

Usage

```
delfplot(parameters)
```

Arguments

parameters A vector of parameters that is generated after estimating the short, intermediate and auxiliary regressions.

Value

A plot object created with ggplot

Examples

```
## Load data set
data("NLSY_IQ")

## Set age and race as factor variables
NLSY_IQ$age <- factor(NLSY_IQ$age)
NLSY_IQ$race <- factor(NLSY_IQ$race)

## Collect parameters from the short, intermediate and auxiliary regressions
parameters <- collect_par(
  data = NLSY_IQ, outcome = "iq_std",
  treatment = "BF_months",
  control = c("age", "sex", "income", "motherAge", "motherEDU", "mom_married", "race"),
  other_regressors = c("sex", "age"))

## Set limits for the bounded box
Rlow <- parameters$Rtilde
Rhigh <- 0.61
deltalow <- 0.01
deltahigh <- 0.99
e <- 0.01

## Oster's method: Plot of delta = f(Rmax)
p4 <- delfplot(parameters = parameters)
print(p4)
```

dplotbate

Histogram of bias adjusted treatment effect

Description

Histogram of bias adjusted treatment effect

Usage

```
dplotbate(data)
```

Arguments

data A data frame that is the output from the "ovbias" function.

Value

A plot object created with ggplot

Examples

```

## Load data set
data("NLSY_IQ")

## Set age and race as factor variables
NLSY_IQ$age <- factor(NLSY_IQ$age)
NLSY_IQ$race <- factor(NLSY_IQ$race)

## Collect parameters from the short, intermediate and auxiliary regressions
parameters <- collect_par(
  data = NLSY_IQ, outcome = "iq_std",
  treatment = "BF_months",
  control = c("age", "sex", "income", "motherAge", "motherEDU", "mom_married", "race"),
  other_regressors = c("sex", "age"))

## Set limits for the bounded box
Rlow <- parameters$Rtilde
Rhigh <- 0.61
deltalow <- 0.01
deltahigh <- 0.99
e <- 0.01

## Not run:
## Compute bias and bias-adjusted treatment effect
OVB <- ovbias(
  parameters = parameters,
  deltalow=deltalow,
  deltahigh=deltahigh, Rhigh=Rhigh,
  e=e)

## Histogram and density Plot of bstar distribution
p3 <- dplotbate(OVB$Data)
print(p3)

## End(Not run)

```

expand_border

Extend border of bounded box by +/- e

Description

Extend border of bounded box by +/- e

Usage

```
expand_border(parameters, deltalow, deltahigh, Rlow, Rhigh, e)
```

Arguments

parameters	A vector of parameters (real numbers) that is generated by estimating the short, intermediate and auxiliary regressions.
deltalow	The lower limit of delta.
deltahigh	The upper limit of delta.
Rlow	The lower limit of Rmax.
Rhigh	The upper limit of Rmax.
e	The step size.

Value

Data frame.

get_border	<i>Identify all border points in a region</i>
------------	---

Description

Identify all border points in a region

Usage

```
get_border(region, e)
```

Arguments

region	A data frame containing the x and y coordinates of the region.
e	The step size of the grid in the x and y directions.

Value

A data frame containing the x and y coordinates of the border points of the region.

mycubic *Compute roots of the cubic equation*

Description

Compute roots of the cubic equation

Usage

```
mycubic(parameters, mydelta, Rmax)
```

Arguments

parameters	A vector of parameters (real numbers) that is generated by estimating the short, intermediate and auxiliary regressions.
mydelta	Value of delta (real number).
Rmax	Value of Rmax (real number).

Value

A vector containing the three roots of the cubic equation defined by the parameters, delta and Rmax.

mydisc *Evaluates discriminant of the cubic equation*

Description

Evaluates discriminant of the cubic equation

Usage

```
mydisc(parameters, mydelta, Rmax)
```

Arguments

parameters	A vector of parameters (real numbers) that is generated by estimating the short, intermediate and auxiliary regressions.
mydelta	The value of delta (real number).
Rmax	The value of Rmax (real number)

Value

Returns a value of 0 or 1; 0 (if discriminant is positive) and 1 (if discriminant is nonpositive)

NLSY_BW

NLSY Birth Weight.

Description

NLSY data to analyse the effect of maternal behaviour on children's birth weight. Natality detail files are from 2001 and 2002. Data is from the NLSY Children and Young Adults panel.

Usage

NLSY_BW

Format

A data frame with 7686 observations on 13 variables:

birth_wt birth weight, grams

BF_months months of breast feeding

mom_drink_preg_all did the mother drink at all during pregnancy

lbw_preterm low birth weight + preterm

age age of child

female child female

black mother black

motherAge age of mother

motherEDU years of schooling of mother

mom_married is the mother married?

income annual income of mother

sex years of schooling of mother

race race of mother

gesweek gestation week

any_smoke did the mother smoke at all during pregnancy

Source: <https://drive.google.com/file/d/101W9dP8F3B1DnAZGBegpoqCfysUrn7Uc/view?usp=sharing>

Examples

```
## Load data set
data("NLSY_BW")
## See names of variables
names(NLSY_BW)
```

NLSY_IQ

NLSY IQ.

Description

NLSY data to analyse the effect of maternal behaviour on children's IQ score. Natality detail files are from 2001 and 2002. Data is from the NLSY Children and Young Adults panel.

Usage

NLSY_IQ

Format

A data frame with 6514 observations on 13 variables:

iq_std standardized IQ score, PIAT score

BF_months months of breast feeding

mom_drink_preg_all did mother drink at all during pregnancy

lbw_preterm low birth weight + preterm

age age of child

female child female

black mother black

motherAge age of mother

motherEDU years of schooling of mother

mom_married is the mother married?

income annual income of mother

sex child sex

race race of mother

Source: <https://drive.google.com/file/d/101W9dP8F3B1DnAZGBegpoqCfysUrn7Uc/view?usp=sharing>

Examples

```
## Load data set
data("NLSY_IQ")
## See names of variables
names(NLSY_IQ)
```

 osterbds

Computes identified set according to Oster (2019)

Description

Computes identified set according to Oster (2019)

Usage

```
osterbds(parameters, Rmax)
```

Arguments

parameters	A vector of parameters that is generated after estimating the short, intermediate and auxiliary regressions.
Rmax	A real number which lies between R_{tilde} (R-squared for the intermediate regression) and 1.

Value

A data frame with three columns:

Discriminant	The value of the discriminant of the quadratic equation that is solved to generate the identified set
Interval1	The interval formed with the first root of the quadratic equation
Interval2	The interval formed with the first root of the quadratic equation

Examples

```
## Load data set
data("NLSY_IQ")

## Set age and race as factor variables
NLSY_IQ$age <- factor(NLSY_IQ$age)
NLSY_IQ$race <- factor(NLSY_IQ$race)

## Collect parameters from the short, intermediate and auxiliary regressions
parameters <- collect_par(
  data = NLSY_IQ, outcome = "iq_std",
  treatment = "BF_months",
  control = c("age", "sex", "income", "motherAge", "motherEDU", "mom_married", "race"),
  other_regressors = c("sex", "age"))

## Oster's method: bounding sets when Rmax=0.61
osterbds(parameters = parameters, Rmax=0.61)
```

osterdelstar	<i>Computes delta* according to Oster (2019)</i>
--------------	--

Description

Computes delta* according to Oster (2019)

Usage

```
osterdelstar(parameters, Rmax)
```

Arguments

parameters	A vector of parameters that is generated after estimating the short, intermediate and auxiliary regressions.
Rmax	A real number that lies between Rtilde (R-squared for the intermediate regression) and 1.

Value

A data frame with three columns:

delstar	The value of delta for the chosen value of Rmax
discontinuity	Indicates whether the point of discontinuity is within the interval formed by Rtilde and 1
slope	Slope of the function, delta=f(Rmax)

Examples

```
## Load data set
data("NLSY_IQ")

## Set age and race as factor variables
NLSY_IQ$age <- factor(NLSY_IQ$age)
NLSY_IQ$race <- factor(NLSY_IQ$race)

## Collect parameters from the short, intermediate and auxiliary regressions
parameters <- collect_par(
  data = NLSY_IQ, outcome = "iq_std",
  treatment = "BF_months",
  control = c("age", "sex", "income", "motherAge", "motherEDU", "mom_married", "race"),
  other_regressors = c("sex", "age"))

## Oster's method: delta* (for Rmax=0.61)
osterdelstar(parameters = parameters, Rmax=0.61)
```

ovbias	<i>Compute bias adjusted treatment effect taking parameter vector as input.</i>
--------	---

Description

Compute bias adjusted treatment effect taking parameter vector as input.

Usage

```
ovbias(parameters, deltalow, deltahigh, Rhigh, e)
```

Arguments

parameters	A vector of parameters (real numbers) that is generated by estimating the short, intermediate and auxiliary regressions.
deltalow	The lower limit of delta.
deltahigh	The upper limit of delta.
Rhigh	The upper limit of Rmax.
e	The step size.

Value

List with three elements:

Data	Data frame containing the bias (\$bias) and bias-adjusted treatment effect (\$bstar) for each point on the grid
bias_Distribution	Quantiles (2.5,5.0,50,95,97.5) of the empirical distribution of bias
bstar_Distribution	Quantiles (2.5,5.0,50,95,97.5) of the empirical distribution of the bias-adjusted treatment effect

Examples

```
## Load data set
data("NLSY_IQ")

## Set age and race as factor variables
NLSY_IQ$age <- factor(NLSY_IQ$age)
NLSY_IQ$race <- factor(NLSY_IQ$race)

## Collect parameters from the short, intermediate and auxiliary regressions
parameters <- collect_par(
  data = NLSY_IQ, outcome = "iq_std",
  treatment = "BF_months",
  control = c("age", "sex", "income", "motherAge", "motherEDU", "mom_married", "race"),
```

```

other_regressors = c("sex","age"))

## Set limits for the bounded box
Rlow <- parameters$Rtilde
Rhigh <- 0.61
deltalow <- 0.01
deltahigh <- 0.99
e <- 0.01

## Not run:
## Compute bias and bias-adjusted treatment effect
OVB <- ovbias(
parameters = parameters,
deltalow=deltalow,
deltahigh=deltahigh, Rhigh=Rhigh,
e=e)

## Default quantiles of bias
(OVB$bias_Distribution)

## Chosen quantiles of bias
quantile(OVB$Data$bias, c(0.01,0.05,0.1,0.9,0.95,0.975))

## Default quantiles of bias-adjusted treatment effect
(OVB$bstar_Distribution)

## Chosen quantiles of bias-adjusted treatment effect
quantile(OVB$Data$bstar, c(0.01,0.05,0.1,0.9,0.95,0.975))

## End(Not run)

```

ovbias_lm	<i>Compute bias adjusted treatment effect taking three lm objects as input.</i>
-----------	---

Description

Compute bias adjusted treatment effect taking three lm objects as input.

Usage

```
ovbias_lm(lm_shrt, lm_int, lm_aux, deltalow, deltahigh, Rhigh, e)
```

Arguments

lm_shrt	lm object corresponding to the short regression
lm_int	lm object corresponding to the intermediate regression
lm_aux	lm object corresponding to the auxiliary regression

deltalow	The lower limit of delta
deltahigh	The upper limit of delta
Rhigh	The upper limit of Rmax
e	The step size

Value

List with three elements:

Data	Data frame containing the bias and bias-adjusted treatment effect for each point on the grid
bias_Distribution	Quantiles (2.5,5.0,50,95,97.5) of the empirical distribution of bias
bstar_Distribution	Quantiles (2.5,5.0,50,95,97.5) of the empirical distribution of the bias-adjusted treatment effect

Examples

```
## Load data set
data("NLSY_IQ")

## Set age and race as factor variables
NLSY_IQ$age <- factor(NLSY_IQ$age)
NLSY_IQ$race <- factor(NLSY_IQ$race)

## Short regression
reg_s <- lm(iq_std ~ BF_months + factor(age) + sex, data = NLSY_IQ)

## Intermediate regression
reg_i <- lm(iq_std ~ BF_months +
  factor(age) + sex + income + motherAge +
  motherEDU + mom_married + factor(race),
  data = NLSY_IQ)

## Auxiliary regression
reg_a <- lm(BF_months ~ factor(age) +
  sex + income + motherAge + motherEDU +
  mom_married + factor(race), data = NLSY_IQ)

## Set limits for the bounded box
Rlow <- summary(reg_i)$r.squared
Rhigh <- 0.61
deltalow <- 0.01
deltahigh <- 0.99
e <- 0.01

## Not run:
## Compute bias and bias-adjusted treatment effect
ovb_lm <- ovbias_lm(lm_shrt = reg_s, lm_int = reg_i,
```



```

lm_aux = reg_a, deltalow=deltalow, deltahigh=deltahigh,
Rhigh=Rhigh, e=e)

## Default quantiles of bias
ovb_lm$bias_Distribution

# Default quantiles of bias-adjusted treatment effect
ovb_lm$bstar_Distribution

## End(Not run)

```

ovbias_par

Compute bias adjusted treatment effect taking data frame as input.

Description

Compute bias adjusted treatment effect taking data frame as input.

Usage

```

ovbias_par(
  data,
  outcome,
  treatment,
  control,
  other_regressors = NULL,
  deltalow,
  deltahigh,
  Rhigh,
  e
)

```

Arguments

data	Data frame.
outcome	Outcome variable.
treatment	Treatment variable.
control	Control variables to add in the intermediate regression.
other_regressors	Subset of control variables to add in the short regression (default is NULL).
deltalow	The lower limit of delta.
deltahigh	The upper limit of delta.
Rhigh	The upper limit of Rmax.
e	The step size.

Value

List with three elements:

Data	Data frame containing the bias and bias-adjusted treatment effect for each point on the grid
bias_Distribution	Quantiles (2.5,5.0,50,95,97.5) of the empirical distribution of bias
bstar_Distribution	Quantiles (2.5,5.0,50,95,97.5) of the empirical distribution of the bias-adjusted treatment effect

Examples

```
## Load data set
data("NLSY_IQ")

## Set parameters for bounded box
Rhigh <- 0.61
deltalow <- 0.01
deltahigh <- 0.99
e <- 0.01

## Not run:
## Compute bias and bias-adjusted treatment effect
OVb_par <- ovbias_par(data=NLSY_IQ,
  outcome="iq_std", treatment="BF_months",
  control=c("age", "sex", "income", "motherAge", "motherEDU", "mom_married", "race"),
  other_regressors = c("sex", "age"), deltalow=deltalow,
  deltahigh=deltahigh, Rhigh=Rhigh, e=e)

## Default quantiles of bias
OVb_par$bias_Distribution

# Default quantiles of bias-adjusted treatment effect
OVb_par$bstar_Distribution

## End(Not run)
```

partocoef

Returns coefficients of the cubic equation

Description

Returns coefficients of the cubic equation

Usage

```
partocoef(parameters, mydelta, Rmax)
```

Arguments

parameters	A vector of parameters (real numbers) that is generated by estimating the short, intermediate and auxiliary regressions.
mydelta	The value of delta (real number)
Rmax	The value of Rmax (real number)

Value

A data frame with the coefficients of the cubic equation.

selectroot	<i>Select root of the cubic based on the root of a nearest point</i>
------------	--

Description

Select root of the cubic based on the root of a nearest point

Usage

```
selectroot(parameters, mydelta, Rmax, closest_bias)
```

Arguments

parameters	A vector of parameters (real numbers) that is generated by estimating the short, intermediate and auxiliary regressions.
mydelta	The value of delta (real number).
Rmax	The value of Rmax (real number).
closest_bias	The value of bias at the nearest point.

Value

Data frame

split_nurr	<i>Split a region into two parts</i>
------------	--------------------------------------

Description

Split a region into two parts

Usage

```
split_nurr(region1, region2, epsilon, parameters, e)
```

Arguments

region1	Data frame with coordinates for region 1
region2	Data frame with coordinates for region 2
epsilon	Closest distance
parameters	A vector of parameters (real numbers) that is generated by estimating the short, intermediate and auxiliary regressions.
e	The step size of the grid in the x and y directions.

Value

List, where first element is region within epsilon distance of region 1 and second element which is region which is not within epsilon distance of region 1.

urrplot	<i>Region plot to demarcate URR and NURR for the bounded box</i>
---------	--

Description

Region plot to demarcate URR and NURR for the bounded box

Usage

```
urrplot(parameters, deltalow, deltahigh, Rlow, Rhigh, e)
```

Arguments

parameters	A vector of parameters (real numbers) that is generated by estimating the short, intermediate and auxiliary regressions.
deltalow	The lower limit for delta.
deltahigh	The upper limit for delta.
Rlow	The lower limit for Rmax.
Rhigh	The upper limit for Rmax.
e	The step size of the grid in the x and y directions.

Value

A plot object created by ggplot

Examples

```
## Load data set
data("NLSY_IQ")

## Set age and race as factor variables
NLSY_IQ$age <- factor(NLSY_IQ$age)
NLSY_IQ$race <- factor(NLSY_IQ$race)

## Collect parameters from the short, intermediate and auxiliary regressions
parameters <- collect_par(
  data = NLSY_IQ, outcome = "iq_std",
  treatment = "BF_months",
  control = c("age", "sex", "income", "motherAge", "motherEDU", "mom_married", "race"),
  other_regressors = c("sex", "age"))

## Set limits for the bounded box
Rlow <- parameters$Rtilde
Rhigh <- 0.61
deltalow <- 0.01
deltahigh <- 0.99
e <- 0.01

## Create region plot for bounded box
p1 <- urrplot(parameters, deltalow, deltahigh, Rlow, Rhigh, e=e)

## See plot
print(p1)
```

Index

* datasets

NLSY_BW, 10

NLSY_IQ, 11

cinhaz, 2

collect_par, 3

cplotbias, 4

delfplot, 5

dplotbate, 6

expand_border, 7

get_border, 8

mycubic, 9

mydisc, 9

NLSY_BW, 10

NLSY_IQ, 11

osterbds, 12

osterdelstar, 13

ovbias, 14

ovbias_lm, 15

ovbias_par, 17

partocoeff, 18

selectroot, 19

split_nurr, 20

urrplot, 20